





Ø Rør	ØI ÷ ØI [mm]	A ± 2 [mm]	B [mm]	S [mm]	C [mm]				FV [Kg]
3/8"	16÷20	54	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
1/2"	20÷24	60	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
3/4"	25÷30	65	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
1"	32÷36	73	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
1.1/4"	38÷44	86	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
1.1/2"	46÷50	91	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
2"	58÷62	106	20	2,0	M6x20	M8	M8 x 80	10 x 50	300
2.1/2"	74÷80	122	30	2,5	M6x20	M10	M10 x 100	12 x 60	300
3"	84÷89	137	30	2,5	M6x20	M10	M10 x 100	12 x 60	300
4"	112÷118	164	30	2,5	M6x20	M10	M10 x 100	12 x 60	300
5"	134÷138	192	30	2,5	M6x20	M10	M10 x 100	12 x 60	400
6"	164÷172	218	30	2,5	M6x20	M10	M10 x 100	12 x 60	400

Fv - carico raccomandato a trazione



Dokumentnr. 832-I	Udgave: A	Side : 1 af 1	Reference standard : ////	VVS-nummer : 017125.xxx
Oprettelse: 11/02/2005	Seneste udgave: 01/01/2013	U.T.		



HYDRAULIC & FIXING SYSTEM

Descrizione:

Rørbærer i rustfri i AISI 304 med ansatsskrue og dybel